


## SOT-89-3L Plastic-Encapsulate MOSFETS

### CJA05N06 N-Channel MOSFET

$V_{(BR)DSS}$	$R_{DS(on)MAX}$	$I_D$
60V	105mΩ@10V	5.5A
	125mΩ@4.5V	



#### DESCRIPTION

The CJA05N06 uses advanced trench technology and design to provide excellent  $R_{DS(on)}$  with low gate charge. This device is suitable for use in a wide variety of applications.


#### FEATURES

- Lead free product is acquired
- Special process technology for high ESD capability
- High density cell design for ultra low  $R_{DS(on)}$
- Good stability and uniformity with high  $E_{AS}$
- Excellent package for good heat dissipation

#### APPLICATION


- Power switching application
- Hard switching and high frequency circuits
- Uninterruptible power supply

#### MARKING



XX: Code

#### Equivalent Circuit



#### Maximum ratings ( $T_a=25^\circ\text{C}$ unless otherwise noted)

Parameter	Symbol	Value	Unit
Drain-Source Voltage	$V_{DS}$	60	V
Gate-Source Voltage	$V_{GS}$	$\pm 20$	V
Continuous Drain Current	$I_D^{(1)}$	5.5	A
Pulsed Drain Current	$I_{DM}^{(2)}$	18	A
Power Dissipation	$P_D^{(1)}$	12.5	W
Thermal Resistance from Junction to Case	$R_{\theta JC}^{(1)}$	10	$^\circ\text{C/W}$
Storage and Junction Temperature	$T_{STG}, T_J$	-55~+150	$^\circ\text{C}$

# MOSFET ELECTRICAL CHARACTERISTICS







$T_J=25^{\circ}\text{C}$  unless otherwise specified

Parameter	Symbol	Test Condition	Min	Typ	Max	Unit	
<b>Off characteristics</b>							
Drain-source breakdown voltage	$V_{(BR)DSS}$	$V_{GS} = 0V, I_D = 250\mu A$	60	-	-	V	
Zero gate voltage drain current	$I_{DSS}$	$V_{DS}=60V, V_{GS}=0V$	$T_J=25^{\circ}\text{C}$	-	-	1.0	$\mu A$
			$T_J=125^{\circ}\text{C}$	-	-	100	
Gate-body leakage current	$I_{GSS}$	$V_{DS} = 0V, V_{GS} = \pm 20V$	-	-	$\pm 100$	nA	
<b>On characteristics</b> <sup>③</sup>							
Gate-threshold voltage	$V_{GS(th)}$	$V_{DS} = V_{GS}, I_D = 250\mu A$	0.5	1.2	2.0	V	
Static drain-source on-resistance	$R_{DS(on)}$	$V_{GS} = 10V, I_D = 3A$	-	72	105	m $\Omega$	
		$V_{GS} = 4.5V, I_D = 3A$	-	83	125	m $\Omega$	
Forward transconductance	$g_{FS}$	$V_{DS} = 15V, I_D = 2A$	1.4	-	-	S	
<b>Dynamic characteristics</b> <sup>④</sup>							
Input capacitance	$C_{iss}$	$V_{DS} = 30V, V_{GS} = 0V, f = 1\text{MHz}$	-	448	-	pF	
Output capacitance	$C_{oss}$		-	26	-		
Reverse transfer capacitance	$C_{rss}$		-	21	-		
<b>Switching characteristics</b> <sup>④</sup>							
Total gate charge	$Q_g$	$V_{DS} = 30V, V_{GS} = 4.5V, I_D = 3A$	-	6	-	nC	
Gate-source charge	$Q_{gs}$		-	1	-		
Gate-drain charge	$Q_{gd}$		-	1.3	-		
Turn-on delay time	$t_{d(on)}$	$V_{DD} = 30V, V_{GS} = 10V, R_G = 1\Omega, I_D = 1.5A$	-	6	-	ns	
Turn-on rise time	$t_r$		-	15	-		
Turn-off delay time	$t_{d(off)}$		-	15	-		
Turn-off fall time	$t_f$		-	10	-		
<b>Drain-Source Diode Characteristics</b>							
Drain-source diode forward voltage	$V_{SD}$ <sup>③</sup>	$V_{GS} = 0V, I_S = 3A$	-	-	1.2	V	
Maximum continuous drain-source diode forward current	$I_S$ <sup>①</sup>		-	-	5.5	A	
Maximum pulsed drain-source diode forward current	$I_{SM}$ <sup>①②</sup>		-	-	18	A	




## Notes :

- $T_C=25^{\circ}\text{C}$  Limited only by maximum temperature allowed.
- $P_W \leq 10\mu s$ , Duty cycle  $\leq 1\%$ .
- Pulse Test : Pulse Width  $\leq 300\mu s$ , duty cycle  $\leq 2\%$ .
- Guaranteed by design, not subject to production.


# Typical Characteristics



# Typical Characteristics




## SOT-89-3L Package Outline Dimensions



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	1.400	1.600	0.055	0.063
b	0.320	0.520	0.013	0.020
b1	0.400	0.580	0.016	0.023
c	0.350	0.440	0.014	0.017
D	4.400	4.600	0.173	0.181
D1	1.550 REF.		0.061 REF.	
E	2.300	2.600	0.091	0.102
E1	3.940	4.250	0.155	0.167
e	1.500 TYP.		0.060 TYP.	
e1	3.000 TYP.		0.118 TYP.	
L	0.900	1.200	0.035	0.047

## SOT-89-3L Suggested Pad Layout



**Note:**


1. Controlling dimension: in millimeters.
2. General tolerance:  $\pm 0.05\text{mm}$ .
3. The pad layout is for reference purposes only.

**NOTICE**

JCET reserves the right to make modifications, enhancements, improvements, corrections or other changes without further notice to any product herein. JCET does not assume any liability arising out of the application or use of any product described herein.

# SOT-89-3L Tape and Reel


## SOT-89-3L Embossed Carrier Tape




**Packaging Description:**  
 SOT-89-3L parts are shipped in tape. The carrier tape is made from a dissipative (carbon filled) polycarbonate resin. The cover tape is a multilayer film (Heat Activated Adhesive in nature) primarily composed of polyester film, adhesive layer, sealant, and anti-static sprayed agent. These reeled parts in standard option are shipped with 1,000 units per 7" or 18.0 cm diameter reel. The reels are clear in color and is made of polystyrene plastic (anti-static coated).

Dimensions are in millimeter										
Pkg type	A	B	C	d	E	F	P0	P	P1	W
SOT-89-3L	4.85	4.45	1.85	Ø1.50	1.75	5.50	4.00	8.00	2.00	12.00

## SOT-89-3L Tape Leader and Trailer



## SOT-89-3L Reel



Dimensions are in millimeter								
Reel Option	D	D1	D2	G	H	I	W1	W2
7" Dia	Ø180.00	60.00	R32.00	R86.50	R30.00	Ø13.00	13.20	16.50

REEL	Reel Size	Box	Box Size(mm)	Carton	Carton Size(mm)	G.W.(kg)
1000 pcs	7 inch	10,000 pcs	203×203×195	40,000 pcs	438×438×220	