



**DFNWB3×3-8L Plastic-Encapsulate MOSFETS**

**CJBE5005 Dual N-Channel MOSFET**


$V_{(BR)DSS}$	$R_{DS(on)TYP}$	$I_D$
20V	9.3 mΩ@4.5V	10A
	9.7mΩ@4.0V	
	10.0mΩ@3.8V	
	10.7mΩ@3.1V	
	12.5mΩ@2.5V	




**DESCRIPTION**

The CJBE5005 uses advanced trench technology to provide excellent  $R_{DS(ON)}$  and low gate charge. It is ESD protected. This device is suitable for use as a uni-directional or bi-directional load switch, facilitated by its common-drain configuration.

**MARKING:**




Top



Back

BE5005 = Part No.  
 Solid dot = Pin1 indicator.  
 XX = Code.

**Equivalent Circuit**



**MAXIMUM RATINGS ( $T_a=25^\circ\text{C}$  unless otherwise noted)**

Parameter	Symbol	Value	Unit
Drain-Source Voltage	$V_{DS}$	20	V
Gate-Source Voltage	$V_{GS}$	$\pm 12$	V
Continuous Drain Current	$I_D$	10	A
Pulsed Drain Current	$I_{DM}^*$	60	A
Thermal Resistance from Junction to Ambient	$R_{\theta JA}$	83.3	$^\circ\text{C/W}$
Junction Temperature	$T_j$	150	$^\circ\text{C}$
Storage Temperature	$T_{stg}$	-55~+150	$^\circ\text{C}$
Lead Temperature for Soldering Purposes(1/8" from case for 10 s)	$T_L$	260	$^\circ\text{C}$

# MOSFET ELECTRICAL CHARACTERISTICS







$T_a=25\text{ }^\circ\text{C}$  unless otherwise specified

Parameter	Symbol	Test Condition	Min	Typ	Max	Unit
<b>STATIC PARAMETERS</b>						
Drain-source breakdown voltage	$V_{(BR)DSS}$	$V_{GS} = 0V, I_D = 250\mu A$	20			V
Zero gate voltage drain current	$I_{DSS}$	$V_{DS} = 16V, V_{GS} = 0V$			1	$\mu A$
Gate-body leakage current	$I_{GSS}$	$V_{GS} = \pm 4.5V, V_{DS} = 0V$			$\pm 1$	$\mu A$
		$V_{GS} = \pm 8V, V_{DS} = 0V$			$\pm 10$	$\mu A$
Gate threshold voltage (note 1)	$V_{GS(th)}$	$V_{DS} = V_{GS}, I_D = 250\mu A$	0.4		1	V
Drain-source on-resistance (note 1)	$R_{DS(on)}$	$V_{GS} = 4.5V, I_D = 5A$	8	9.3	11.5	$m\Omega$
		$V_{GS} = 4.0V, I_D = 5A$	8.2	9.7	12.5	$m\Omega$
		$V_{GS} = 3.8V, I_D = 5A$	8.5	10.0	13	$m\Omega$
		$V_{GS} = 3.1V, I_D = 5A$	9	10.7	14	$m\Omega$
		$V_{GS} = 2.5V, I_D = 5A$	9.5	12.5	17	$m\Omega$
Forward transconductance (note 1)	$g_{FS}$	$V_{DS} = 5V, I_D = 7A$	9	36		S
Diode forward voltage(note 1)	$V_{SD}$	$I_S = 1A, V_{GS} = 0V$			1	V
<b>DYNAMIC PARAMETERS (note 2)</b>						
Input Capacitance	$C_{iss}$	$V_{DS} = 10V, V_{GS} = 0V, f = 1MHz$		1700		$\mu F$
Output Capacitance	$C_{oss}$			230		$\mu F$
Reverse Transfer Capacitance	$C_{rss}$			200		$\mu F$
Total gate charge	$Q_g$	$V_{DS} = 10V, V_{GS} = 4.5V, I_D = 7A$		17		nC
Gate-source charge	$Q_{gs}$			1.5		nC
Gate-drain charge	$Q_{gd}$			4.7		nC
<b>SWITCHING PARAMETERS (note 2)</b>						
Turn-on delay time	$t_{d(on)}$	$V_{GS} = 5V, V_{DD} = 10V,$ $R_L = 1.35\Omega, R_{GEN} = 3\Omega$		2.5		ns
Turn-on rise time	$t_r$			7.2		ns
Turn-off delay time	$t_{d(off)}$			49		ns
Turn-off fall time	$t_f$			108		ns
<b>Drain-Source Diode Characteristics</b>						
Diode Forward Current	$I_S$		-	-	8.0	A

**Notes :**


1. Pulse Test : Pulse width  $\leq 300\mu s$ , duty cycle  $\leq 0.5\%$ .
2. Guaranteed by design, not subject to production testing.

# Typical Characteristics




# Typical Characteristics


TOTAL POWER DISSIPATION vs. AMBIENT TEMPERATURE




Maximum Safe Operating Area




CJBE5005  $R_{DS(on)}$  vs.  $T_A$




## DFNWB3×3-8L-K Package Outline Dimensions(Unit:mm)



TOP VIEW




BOTTOM VIEW



SIDE VIEW

SYMBOL	MILLIMETER		
	MIN	NOM	MAX
A	0.70	0.75	0.80
A1	0.00	0.02	0.05
b	0.25	0.30	0.35
c	0.19	0.20	0.21
D	2.90	3.00	3.10
Nd	1.90	1.95	2.00
E	2.90	3.00	3.10
e	0.65BSC		
L	0.37	0.42	0.47
h	0.10	0.15	0.20
载体尺寸 (mil)	102X84		

## DFNWB3×3-8L-K Suggested Pad Layout



**Note:**

1. Controlling dimension: in millimeters.
2. General tolerance:  $\pm 0.050\text{mm}$ .
3. The pad layout is for reference purposes only.

**NOTICE**

JSCJ reserves the right to make modifications, enhancements, improvements, corrections or other changes without further notice to any product herein. JSCJ does not assume any liability arising out of the application or use of any product described herein.