



TO-252-2L Plastic-Encapsulate Diode

MURD10H20CT HYPERFAST RECTIFIER, FRED

MAIN CHARACTERISTICS

I_o	10(5×2)A
V_{RRM}	200V
T_{rr}	13ns
T_j	175°C
$V_{F(typ)}$	0.7V(@$T_j=150°C$)


FEATURES

- Ultrafast Recovery Times and Low Recovery Loss
- Low Forward Voltage
- Low Reverse Leakage Current


APPLICATIONS

Specifically designed to improve efficiency of PFC and output rectification stages of EV / HEV battery charging stations, booster stage of solar inverters and UPS applications, these devices are perfectly matched to operate with MOSFETs or high speed IGBTs.

MARKING



MURD10H20CT = Device code
 Solid dot = Green molding compound device
 if none, the normal device
 XXXX = Code



MAXIMUM RATINGS ($T_c=25°C$ unless otherwise noted)

Symbol	Parameter	MURD10H20CT	Unit
V_{RRM}	Peak Repetitive Reverse Voltage	200	V
V_R	DC Blocking Voltage		
$I_{F(AV)}$	Average rectified output current@ Per leg($T_c=161°C$)	5	A
	Average rectified output current@ Total device($T_c=161°C$)	10	
$I_{F(RMS)}$	RMS Forward Current($T_c=161°C$)	7	A
I_{FSM}	Non-Repetitive Surge Forward Current (8.3ms)	120	A
P_D	Power dissipation	38	W
$R_{\theta JC}$	Thermal Resistance From Junction to Case@ Per leg	4.0	°C/W
T_j	Operating Junction Temperature Range	-55 ~ +175	°C
T_{stg}	Storage Temperature Range	-55 ~ +175	°C


Typical Characteristics

ELECTRICAL CHARACTERISTICS ($T_C=25^\circ\text{C}$ unless otherwise specified)

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
$V_{(BR)}$	Reverse Voltage	$I_R=100\mu\text{A}$	200			V
I_R	Reverse Current	$V_R=200\text{V}$	$T_j=25^\circ\text{C}$		5	μA
			$T_j=150^\circ\text{C}$		500	μA
V_F	Forward Voltage	$I_F=5\text{A}$	$T_j=25^\circ\text{C}$	0.9	1.0	V
			$T_j=150^\circ\text{C}$	0.7		V
C_{tot}	Total Capacitance	$V_R=200\text{V}, f=1\text{MHz}$		14.5		pF
t_{rr}	Reverse Recovery time	$I_F=0.5\text{A}, I_R=1\text{A}, I_{rr}=0.25\text{A}$		18		ns
		$I_F=1\text{A}, V_R=30\text{V}, di_F/dt = 200\text{A}/\mu\text{s}$		13		ns

ELECTRICAL CHARACTERISTICS ($T_C=25^\circ\text{C}$ unless otherwise specified)


Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
t_{rr}	Reverse Recovery Time	$I_F=10\text{A}, V_R=100\text{V}, di_F/dt=200\text{A}/\mu\text{s}$		16		ns
I_{RRM}	Max. Reverse Recovery Current			3.0		A
Q_{rr}	Reverse Recovery Charge			27		nC
t_{rr}	Reverse Recovery Time	$I_F=10\text{A}, V_R=100\text{V}, di_F/dt=200\text{A}/\mu\text{s}, T_j=125^\circ\text{C}$		28		ns
I_{RRM}	Max. Reverse Recovery Current			5.5		A
Q_{rr}	Reverse Recovery Charge			80		nC
t_{rr}	Reverse Recovery Time	$I_F=10\text{A}, V_R=100\text{V}, di_F/dt=500\text{A}/\mu\text{s}, T_j=125^\circ\text{C}$		24		ns
I_{RRM}	Max. Reverse Recovery Current			11		A
Q_{rr}	Reverse Recovery Charge			145		nC




Reverse Recovery Waveform and Definitions

Typical Characteristics


Forward Characteristics




Reverse Characteristics




Capacitance Characteristics Per Diode




Recovery Current vs. di_F/dt



Reverse Recovery Time vs. di_F/dt




Stored Charge vs. di_F/dt




Typical Characteristics


Dynamic Parameters vs. Junction Temperature




Current Derating



MURD10H20CT Transient Thermal Impedance, Junction-Case




TO-252-2L Package Outline Dimensions



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	2.200	2.400	0.087	0.094
A1	0.000	0.127	0.000	0.005
b	0.635	0.770	0.025	0.030
c	0.460	0.580	0.018	0.023
D	6.500	6.700	0.256	0.264
D1	5.100	5.460	0.201	0.215
D2	4.830 REF.		0.190 REF.	
E	6.000	6.200	0.236	0.244
e	2.186	2.386	0.086	0.094
L	9.712	10.312	0.382	0.406
L1	2.900 REF.		0.114 REF.	
L2	1.400	1.700	0.055	0.067
L3	1.600 REF.		0.063 REF.	
L4	0.600	1.000	0.024	0.039
phi	1.100	1.300	0.043	0.051
theta	0°	8°	0°	8°
h	0.000	0.300	0.000	0.012
V	5.250 REF.		0.207 REF.	

TO-252-2L Suggested Pad Layout



Note:

1. Controlling dimension: in millimeters.
2. General tolerance: ± 0.05 mm.
3. The pad layout is for reference purposes only.

NOTICE

JSCJ reserves the right to make modifications, enhancements, improvements, corrections or other changes without further notice to any product herein. JSCJ does not assume any liability arising out of the application or use of any product described herein.

TO-252-2L Tape and Reel

TO-252-2L Embossed Carrier Tape




Packaging Description:

TO-252-2L parts are shipped in tape. The carrier tape is made from a dissipative (carbon filled) polycarbonate resin. The cover tape is a multilayer film (Hear Activated Adhesive in nature) primarily composed of polyester film, adhesive layer, sealant, and anti-static sprayed agent. These reeled parts in standard option are shipped with 2500 units per 13" or 33.0 cm diameter reel. The reels are clear in color and is made of polystyrene plastic (anti-static coated).

Dimensions are in millimeter										
Pkg type	A	B	C	d	E	F	P0	P	P1	W
TO-252	6.90	10.50	2.70	Φ1.55	1.75	7.50	4.00	8.00	2.00	16.00

TO-252-2L Tape Leader and Trailer



TO-252-2L Reel



Dimensions are in millimeter						
Reel	D	D1	D2	W1	W2	l
13" Dia	330.00	100.00	Φ21.00	16.40	21.40	Φ13.00

Reel	Reel Size	Box	Box Size(mm)	Carton	Carton Size(mm)
2500 pcs	13 inch	5000 pcs	360×360×65	25000 pcs	378×358×382