

TO-220F-B Plastic-Encapsulate Diode

MURF30H20CTB HYPERFAST RECTIFIER, FRED

MAIN CHARACTERISTICS

| | |
|--------------|--------------------------------------|
| I_o | 30(15×2)A |
| V_{RRM} | 200V |
| T_{rr} | 23ns |
| T_j | 175℃ |
| $V_{F(typ)}$ | 0.75V(@$T_j=150℃$) |


FEATURES

- Ultrafast Recovery Times and Low Recovery Loss
- Low Forward Voltage
- Low Reverse Leakage Current


APPLICATIONS

Specifically designed to improve efficiency of PFC and output rectification stages of EV / HEV battery charging stations, booster stage of solar inverters and UPS applications, these devices are perfectly matched to operate with MOSFETs or high speed IGBTs.

MARKING



MURF30H20CTB = Device code
 Solid dot = Green molding compound device
 if none, the normal device
 XXXX = Code



MAXIMUM RATINGS ($T_c=25℃$ unless otherwise noted)

| Symbol | Parameter | MURF30H20CTB | Unit |
|-----------------|--|--------------|------|
| V_{RRM} | Peak Repetitive Reverse Voltage | 200 | V |
| V_R | DC Blocking Voltage | | |
| $I_{F(AV)}$ | Average rectified output current@ Per leg($T_c=130℃$) | 15 | A |
| | Average rectified output current@ Total device($T_c=130℃$) | 30 | |
| $I_{F(RMS)}$ | RMS Forward Current($T_c=130℃$) | 21 | A |
| I_{FSM} | Non-Repetitive Surge Forward Current (8.3ms) | 260 | A |
| P_D | Power dissipation | 34 | W |
| $R_{\theta JC}$ | Thermal Resistance From Junction to Case@ Per leg | 4.4 | ℃/W |
| T_j | Operating Junction Temperature Range | -55 ~ +175 | ℃ |
| T_{stg} | Storage Temperature Range | -55 ~ +175 | ℃ |


Typical Characteristics

ELECTRICAL CHARACTERISTICS ($T_c=25^\circ\text{C}$ unless otherwise specified)

| Symbol | Parameter | Test Conditions | Min. | Typ. | Max. | Unit |
|------------|-----------------------|--|-------------------------|------|------|---------------|
| $V_{(BR)}$ | Reverse Voltage | $I_R=100\mu\text{A}$ | 200 | | | V |
| I_R | Reverse Current | $V_R=200\text{V}$ | $T_j=25^\circ\text{C}$ | | 5 | μA |
| | | | $T_j=150^\circ\text{C}$ | | 500 | μA |
| V_F | Forward Voltage | $I_F=15\text{A}$ | $T_j=25^\circ\text{C}$ | 0.95 | 1.1 | V |
| | | | $T_j=150^\circ\text{C}$ | 0.75 | | V |
| C_{tot} | Total Capacitance | $V_R=200\text{V}, f=1\text{MHz}$ | | 54.8 | | pF |
| t_{rr} | Reverse Recovery time | $I_F=0.5\text{A}, I_R=1\text{A}, I_{rr}=0.25\text{A}$ | | 26 | | ns |
| | | $I_F=1\text{A}, V_R=30\text{V}, di_F/dt = 200\text{A}/\mu\text{s}$ | | 23 | | ns |

ELECTRICAL CHARACTERISTICS ($T_c=25^\circ\text{C}$ unless otherwise specified)


| Symbol | Parameter | Test Conditions | Min. | Typ. | Max. | Unit |
|-----------|-------------------------------|---|------|------|------|------|
| t_{rr} | Reverse Recovery Time | $I_F=15\text{A}, V_R=100\text{V}, di_F/dt=200\text{A}/\mu\text{s}$ | | 13 | | ns |
| I_{RRM} | Max. Reverse Recovery Current | | | 1.9 | | A |
| Q_{rr} | Reverse Recovery Charge | | | 14 | | nC |
| t_{rr} | Reverse Recovery Time | $I_F=15\text{A}, V_R=100\text{V}, di_F/dt=200\text{A}/\mu\text{s}, T_j=125^\circ\text{C}$ | | 27 | | ns |
| I_{RRM} | Max. Reverse Recovery Current | | | 4.7 | | A |
| Q_{rr} | Reverse Recovery Charge | | | 67 | | nC |
| t_{rr} | Reverse Recovery Time | $I_F=15\text{A}, V_R=100\text{V}, di_F/dt=500\text{A}/\mu\text{s}, T_j=125^\circ\text{C}$ | | 23 | | ns |
| I_{RRM} | Max. Reverse Recovery Current | | | 11 | | A |
| Q_{rr} | Reverse Recovery Charge | | | 132 | | nC |




Reverse Recovery Waveform and Definitions

Typical Characteristics


Forward Characteristics




Reverse Characteristics




Capacitance Characteristics Per Diode




Recovery Current vs. di_F/dt



Reverse Recovery Time vs. di_F/dt




Stored Charge vs. di_F/dt




Typical Characteristics


Dynamic Parameters vs. Junction Temperature




Current Derating



MURF30H20CTB Transient Thermal Impedance, Junction-Case



TO-220F-B Package Outline Dimensions



| Symbol | Dimensions In Millimeters | | Dimensions In Inches | |
|--------|---------------------------|--------|----------------------|-------|
| | Min. | Max. | Min. | Max. |
| A | 4.300 | 4.700 | 0.169 | 0.185 |
| A1 | 1.200 REF. | | 0.047 REF. | |
| A2 | 2.800 | 3.200 | 0.110 | 0.126 |
| A3 | 2.500 | 2.900 | 0.098 | 0.114 |
| b | 0.710 | 0.910 | 0.028 | 0.036 |
| b1 | 1.100 | 1.350 | 0.043 | 0.053 |
| B1 | 1.150 | 1.400 | 0.045 | 0.055 |
| c | 0.500 | 0.750 | 0.020 | 0.030 |
| D | 9.960 | 10.360 | 0.392 | 0.408 |
| E | 14.800 | 15.200 | 0.583 | 0.598 |
| e | 2.540 TYP. | | 0.100 TYP. | |
| F | 2.700 REF. | | 0.106 REF. | |
| Φ | 3.300 | 3.700 | 0.130 | 0.146 |
| L | 28.000 | 28.400 | 1.102 | 1.118 |
| L1 | 2.100 | 2.400 | 0.082 | 0.094 |
| L2 | 1.300 | 1.700 | 0.051 | 0.066 |